


# Counter balanced lift crane with telescopic boom

## Immagini Prodotto



## Descrizione

Crane with a reversed boom and counterweight with a capacity of up to 1000 kg and a boom length up to 2000 mm

Reversed boom design eliminates front leg interference, allowing crane to get into, under and over obstacles in tight spaces.

Provides safe, easy lifting in production areas and warehouse with simple hand operated hydraulic lift. The long boom grants an easy access also to distant positions.

Rolls smoothly on 2 fixed casters Ø 250mm and 2 swivel casters Ø 200mm with brake. Very good maneuverability even at full load.

Double acting pump can be operated with a minimum effort.

The load is lowered by opening the relief valve: the operator can choose the lowering speed gradually opening or closing the valve.

The boom length can be adjusted on 4 different positions.

2 fixed casters d. 250 mm e 2 swivel casters with brake Ø 200

**Overall sizes** mm 2990x805x1920

**Boom length** mm 1250

**Boom length with boom extension** a mm 2000

**Weight** kg 1150

**Capacity** kg 1000

**Maximum pressure** bar 95

**Tank volume** l 3

Optional: Boom extensio with length up to 2000 mm, with a capacity up to 250 kg.

THE OPERATOR DOES NOT NEED A LICENSE OR TO ATTEND ANY TRAINING COURSE

EPOXY POWDER COATED

COMPLIANT TO CE RULES

<b>CILINDRO</b>		
<b>Corsa</b>	<b>Ø</b>	<b>Ø Stelo</b>
(mm)	(mm)	(mm)
550	50	70

<b>MAXIMUM CAPACITY AT DIFFERENT BOOM LENGTH (WI TH BOOM EXTENSION)</b>		
<b>Position</b>	<b>Length</b>	<b>Capacity</b>
	(mm)	(kg)
1	1400	450
2	1600	390
3	1800	325
4	2000	275

MAXIMUM CAPACITY AT DIFFERENT BOOM LENGTH (STANDARD BOOM)		
Position	Length	Capacity
	(mm)	(kg)
1	650	1000
2	850	835
3	1050	670
4	1250	500

## Informazioni Aggiuntive

Cod. Prod.	GRUCP10
Fornito	Montato - Pronto all'uso
Weight kg	1150.0000
Load Capacity	1000
Colour	Yellow RAL028
Manufacturer	Carmeccanica
Made in	Italia
Warranty	2 Years
Conformità	CE
Lead Time	Su Richiesta