


Counter balanced lift crane with telescopic boom

Immagini Prodotto



Descrizione

Crane with a reversed boom and counterweight with a capacity of up to 1000 kg and a boom length up to 2000 mm

Reversed boom design eliminates front leg interference, allowing crane to get into, under and over obstacles in tight spaces.

Provides safe, easy lifting in production areas and warehouse with simple hand operated hydraulic lift. The long boom grants an easy access also to distant positions.

Rolls smoothly on 2 fixed casters Ø 250mm and 2 swivel casters Ø 200mm with brake. Very good maneuverability even at full load.

Double acting pump can be operated with a minimum effort.

The load is lowered by opening the relief valve: the operator can choose the lowering speed gradually opening or closing the valve.

The boom length can be adjusted on 4 different positions.

2 fixed casters d. 250 mm e 2 swivel casters with brake Ø 200

Overall sizes mm 2990x805x1920

Boom length mm 1250

Boom lenght with boom extension a mm 2000

Weight kg 1150

Capacity kg 1000

Maximum pressure bar 95

Tank volume l 3

Optional: Boom exstensio with lenght up to 2000 mm, with a capacity up to 250 kg.

THE OPERATOR DOES NOT NEED A LICENSE OR TO ATTEND ANY TRAINING COURSE

EPOXY POWDER COATED

COMPLIANT TO CE RULES

CILINDRO		
Corsa	Ø	Ø Stelo
(mm)	(mm)	(mm)
550	50	70

MAXIMUM CAPACITY AT DIFFERENT BOOM LENGTH (WI TH BOOM EXTENSION)		
Position	Length	Capacity
	(mm)	(kg)
1	1400	450
2	1600	390
3	1800	325
4	2000	275

MAXIMUM CAPACITY AT DIFFERENT BOOM LENGTH (STANDARD BOOM)		
Position	Length	Capacity
	(mm)	(kg)
1	650	1000
2	850	835
3	1050	670
4	1250	500

Informazioni Aggiuntive

Cod. Prod.	GRUCP10
Fornito	Montato - Pronto all'uso
Weight kg	1150.0000
Load Capacity	1000
Colour	Yellow RAL028
Manufacturer	Carmeccanica
Made in	Italia
Warranty	2 Years
Conformità	CE
Lead Time	Su Richiesta