

# Rubber wheel tyre Ø 200x50

## Immagini Prodotto



## Descrizione

Temperature range: between -20 and +60°C.

Rubber tyre hardness: 82 ± 4 Sh A.

Hub in zinc-chromated and riveted pressed steel sheet.

Standar roller bearing

Black solid rubber tyre with trapezoidal profile

Wheel centre formed from two zinc plated pressed steel discs riveted together.

Maximum working speed: 4 Km/h.

Applications: Hand trolleys for medium loads.

Contact should be avoided with Grease, Oils, Hydrocarbons, Chloride & Aromatic solvents.

Wheels suitable for stoneware, asphalt, concrete and resin.

## Informazioni Aggiuntive

Cod. Prod.	R200SRRU
Made in	Italia
Lead Time	Pronta Consegna
Type of Wheel:	Rubber
Tipo Cerchio	Ferro
Diametro Ruota in mm	200
Fascia Ruota mm	50
Rotolamento su	Cuscinetti a Rulli
Weight kg	3.2000
Portata DaN	230
Altezza supporto mm	-
Dimensioni piastra mm	-
Interasse fori (AxB) mm	-
Diametro foro piastra mm	-
Disassamento mm	-
Raggio d'ingombro leva freno anteriore mm	-
Raggio d'ingombro leva freno posteriore mm	-