

Self propelled electric power pallet truck

Immagini Prodotto



Descrizione

TNBTX

20

FEATURES

Capacity	Q	Kg	2.000
Load center distance	C	mm	600
Drive system			Fold down rider platform

SIZES

Lift height	h3	mm	120
Free lift		mm	
Overall fork length	l	mm	1.150
Width over forks	b5	mm	540
Fork width x thickness	e7s	mm	160/60
Total length (folded rider platform)	l1	mm	1.815
Length to front face of forks	l 2	mm	665
Width	b 1	mm	726
Minimum height	h1	mm	745
Tiller height in neutral position	h 4	mm	1.323
Turning radius	Wa	mm	1.640
Handle height MAX/min	h 14	mm	1.320/940
Minimum fork height	h 13	mm	85
Working aisle pallet 800x1200	AST	mm	2.105

PERFORMANCES

Drive speed loaded/ unloaded		Km/h	5.0/5.2
Lifting speed loaded/unloaded		mm/s	27/35
Lowering speed loaded/ unloaded	y	mm/s	42/27

Gradeability

CHASSIS

Wheels number drive end/ load end	nr	2+1M/4
Polyurethane stabilizer caster	mm Ø	100x40
Drive wheel	mm Ø	230x75
Nylon front rollers	mm Ø	84x70
Wheelbase	y mm	1.368
Track width drive end	b 10 mm	540
Track width fork end	b 11 mm	380

MOTOR

Drive motor s2 60 min	Kw	1,5
Lifting motor s3 15%	Kw	0,8
Drive control		MOSFET
Battery	V/Ah	24/210

WEIGHT

Weight unloaded	Kg	634
Weight battery	Kg	185

RECTIFIER

Charger	V-A	24-40
---------	-----	-------

Informazioni Aggiuntive

Cod. Prod.	TE1000
Fornito	Montato - Pronto all'uso
Weight kg	62.0000
Load Capacity	1000
Colour	Red RAL3000
Manufacturer	Carmeccanica
Made in	Italia
Warranty	Legale
Conformità	n.a.
Lead Time	Esaurito