



Self propelled stacker

Immagini Prodotto



Descrizione

TNBEXS

12/29AL

FEATURES

Capacity	Q	Kg	1.200
Load center distance	C	mm	600
Drive			Fold down rider platform

SIZES

Lifting height	h3	mm	2.820
Free lift		mm	1.490
Overall fork length	l	mm	1.150
Width over forks	b5	mm	570
Fork width x thickness	e7s	mm	180/60
Overall length (TOEPLATE closed)	l1	mm	1.908
Length to front face of forks	l 2	mm	758
Width	b 1	mm	890
Minimum height	h1	mm	1.976
Maximum overall height	h 4	mm	3.276
Turning radius	Wa	mm	1.280
Tiller height MAX/min	h 14	mm	1.320/940
Minimum fork height	h 13	mm	81
Working aisle pallet 800x1200	AST	mm	2.158

PERFORMANCES

Drive speed loaded/ unloaded		Km/h	5.2/5.5
Lifting speed loaded/unloaded		mm/s	110/170
Lowering speed loaded/ unloaded	y	mm/s	120/130

Gradeability loaded/unloaded

CHASSIS

Wheels number drive end/ load end	nr		2+1M/4
Polyurethane stabilizer caster	mm Ø		150x54
Drive wheel	mm Ø		252x89
Nylon front rollers	mm Ø		80x70
Wheelbase	y	mm	1.278
Truck width drive end	b 10	mm	650
Truck width load end	b 11	mm	390

MOTOR

Drive motor s2 60 min	Kw		1.3
Lifting motor s3 15%	Kw		2.2
Drive control			MOSFET
Battery	V/Ah		24/210

WEIGHT

Weight unloaded	Kg		910
Weight battery	Kg		185

RECTIFIER

Charger	V-A		24-40
---------	-----	--	-------

Informazioni Aggiuntive

Cod. Prod.	TNBEXS 12/29AL
GTIN/EAN	8053853156266
Fornito	Montato - Pronto all'uso
Weight kg	910.0000
Type of Wheel:	-
Colour	Red RAL3000
Manufacturer	Carmeccanica
Warranty	2 Years
Conformità	CE
Lead Time	Esaurito